



**NOTES:**

1. All driveways must meet the current Town driveway requirements and NCDOT requirements for spacing, sight distance, and offsets from property lines and intersections.
2. Special conditions may warrant exceptions to this detail. Subject to approval by Town Engineering or Public Works Director.
3. Driveway width shall not exceed 36' when not served by tractor/trailer traffic (AASHTO WB-40)\*.
4. Driveway width shall not exceed 40' when served by tractor/trailer traffic (AASHTO WB-40)\*\*.
5. Driveway aprons shall be constructed of a min. 4" thick, 3000 psi concrete or 6" ABC base course with a 2" asphalt surface course.



TOWN OF NAGS HEAD  
 DEPARTMENT OF ADMINISTRATION  
 P.O. BOX 99  
 NAGS HEAD, NC 27959  
 252.441.7016 • www.nagsheadnc.gov

**TYPICAL COMMERCIAL DRIVEWAY DETAIL**  
**SMALL PARKING LOT LAYOUT**  
 (FOR SMALL PARKING LOTS WITH LESS THAN 36 PARKING STALLS)

SCALE: NONE  
 ISSUE DATE: 7-9-2015  
 REVISION DATE: 1-3-2019  
 SHEET NO: 1 OF 1  
 DRAWN BY: DMR

DETAIL NO.:  
**200**  
 12