



NOTE:

A 0.18 TO 0.45 GAL/SYD PRIME COAT IS REQUIRED ON AGGREGATE BASE COURSE. THE PAVEMENT DESIGN SHOWN ARE MINIMUM THICKNESSES AND SHOULD BE DESIGNED BASED UPON SUBGRADE SOIL CONDITIONS AND PLANNED TRAFFIC LOADING IMPACTS. NO BASE COURSE SHALL BE PLACED ON MUCK, CLAY, ORGANIC MATTER OR OTHER UNSUITABLE MATERIAL. OTHER BASE COURSES MAY BE USED IN LIEU OF THOSE SHOWN ABOVE. ALTERNATE MATERIALS SHALL BE OF SUFFICIENT THICKNESS TO PROVIDE EQUIVALENT STRENGTH AND SHALL BE APPROVED BY THE TOWN ENGINEER.



TOWN OF NAGS HEAD
 DEPARTMENT OF ADMINISTRATION
 P.O. BOX 99
 NAGS HEAD, NC 27959
 252.441.7016 • www.nagsheadnc.gov

**ENVIRONMENTAL & SUBCOLLECTOR STREETS
 TYPICAL CROSS SECTION**

SCALE: NONE
 ISSUE DATE: 1-29-2019
 REVISION DATE: 1-29-2019
 SHEET NO: 1 OF 1
 DRAWN BY: DMR

DETAIL NO.:

303